AMENDMENTS TO THE CLAIMS

The following listing of claims replaces all prior listings, and all prior versions, of claims in the application.

LISTING OF CLAIMS:

- 1. 6. (Cancelled).
- 7. (Currently Amended) Biological photometric equipment comprising:

a light irradiating unit for irradiating a trial subject with mixed light obtained by mixing light in a first wavelength range having a peak wavelength at a first wavelength and light in a second wavelength range having a peak wavelength at a wavelength longer than the first wavelength; and

a light receiving unit, <u>adapted to be</u> disposed on said trial subject, for detecting transmitted light irradiated from said light irradiating unit and propagating into the inside of said trial subject;

wherein a value of said first wavelength is in the range from 650 nm to 800 nm and a value of said second wavelength is in the range from 810 nm to 900 nm;

a unit for changing a ratio of irradiated light intensities for measuring biological information concerning density of a light-absorbing material or changes in the densities in said trial subject is measured based on transmitted signals detected by said light receiving unit;

maintaining a sum of intensity of the irradiated light in said first wavelength range at a region X on the trial subject irradiated with the light and intensity of the irradiated light in said second wavelength range is kept not higher than a , prespecified value; and

said equipment further comprises a unit for changing a ratio of irradiated light intensities so that wherein said intensity of irradiated light in said first wavelength range at said region x is at least either in the range from 0.3 to 0.7 time-times or in the range from 1.3 to 19 times as compared to that of irradiated light in said, second wavelength range.

- 8. (Currently Amended) The biological photometric equipment according to claim 1claim 7, wherein said equipment further comprises a unit for changing a ratio the ratio of irradiated light intensities changes said ratio so that the intensity of irradiated light in said first wavelength range at said region X is at least either in the range from 0.3 to 0.7 time-times or in the range from 1.3 to 10 times as compared to that of irradiated light in said second wavelength range when a value of said first wavelength is in the range from 700 nm to 790 nm.
- 9. (Currently Amended) The biological photometric equipment according to claim 1 claim 7 further comprising:

a unit for calculating a measurement error included in the biological information obtained from a measured living body;

a unit for calculating a ratiothe ratio of irradiated light intensities required for setting a setting the measurement error included in information obtained from the measured living body; and

a unit for adjusting the irradiated light intensities based on a result of said ealculationcalculations.

10. (Currently Amended) The biological photometric equipment according to elaim 1claim 7 further comprising:

a unit for switching the ratio of irradiated light intensities from time to time between a and b and "b", wherein sign a denotes a ratio of irradiated light in the first wavelength range against irradiated light in the second wavelength range at said region X substantially minimizing a measurement error included in a first information obtained from a first the measured living bodytrial subject, and sign b denotes a ratio of irradiated light in the first wavelength range against irradiated light in the second wavelength range at said region X substantially minimizing a measurement error included in a second information obtained from a second the measured living bodytrial subject.

- 11. (Currently Amended) The biological photometric equipment according to claim 4claim 10, wherein the first information obtained from said first living bodythe measured trial subject relates to density or changes in density of oxygenated hemoglobin, and the second information obtained from said second living bodythe measured trial subject relates to density or changes in density of deoxygenated hemoglobin.
- 6-12. (Currently Amended) The biological, photometric equipment according to claim 1 claim 7 further comprising an anchoring tool holding a plurality of said light irradiating units and said light receiving units and configured to be set on a head portion of a trial the trial subject, wherein said anchoring tool has a plurality said

Docket No. 520.46162X00 Serial No. 10/577,944 Office Action dated December 6, 2010

plurality of holes provided thereon for setting therein optical fibers for a for said plurality of light irradiating units and a plurality of light receiving units alternately provided in lattice form.